

# BULLET<sup>5</sup>

UBIQUITI NETWORKS 

Zero Variable Wireless Deployments



SYSTEM INFORMATION	
Processor Specs	Atheros SOC, MIPS 4KC, 180MHz
Memory Information	16MB SDRAM, 4MB Flash
Networking Interface	10/100 BASE-TX (Cat. 5, RJ-45) Ethernet Interface

REGULATORY / COMPLIANCE INFORMATION	
Wireless Modular Approvals	FCC Part 15.247, IC RS210, CE
RoHS Compliance	YES

RADIO OPERATING FREQUENCY 5.475-5.825GHz							
TX SPECIFICATIONS				RX SPECIFICATIONS			
	DataRate	Avg.Power	Tolerance		DataRate	Sensitivity	Tolerance
802.11a OFDM	6Mbps	22 dBm	+/-1.5dB	802.11a OFDM	6Mbps	-94 dBm	+/-1.5dB
	9Mbps	22 dBm	+/-1.5dB		9Mbps	-93 dBm	+/-1.5dB
	12Mbps	22 dBm	+/-1.5dB		12Mbps	-91 dBm	+/-1.5dB
	18Mbps	22 dBm	+/-1.5dB		18Mbps	-90 dBm	+/-1.5dB
	24Mbps	22 dBm	+/-1.5dB		24Mbps	-86 dBm	+/-1.5dB
	36Mbps	20 dBm	+/-1.5dB		36Mbps	-83 dBm	+/-1.5dB
	48Mbps	19 dBm	+/-1.5dB		48Mbps	-77 dBm	+/-1.5dB
	54Mbps	17 dBm	+/-1.5dB		54Mbps	-74 dBm	+/-1.5dB

ADJUSTABLE CHANNEL SIZE SUPPORT			
5MHz	10MHz	20MHz	40MHz

RANGE PERFORMANCE	
Outdoor (Antenna Dependent):	Over 50km

PHYSICAL / ELECTRICAL / ENVIRONMENTAL	
RF Connector	Integrated N-type Male Jack (connects directly to antenna)
Enclosure Size	15.2cm. length x 3.1 cm. height x 3.7cm. width
Weight	0.18kg
Enclosure Characteristics	Outdoor UV Stabilized Plastic
Max Power Consumption	4 Watts
Power Rating	Up to 24V
Power Method	Passive Power over Ethernet (pairs 4,5+; 7,8 return)
Operating Temperature	-20C to +70C
Operating Humidity	5 to 95% Condensing
Shock and Vibration	ETSI300-019-1.4

SOFTWARE



visit [www.ubnt.com/airos](http://www.ubnt.com/airos)